

## SPECIFICATION DATA SHEET

### MEDITRAC<sup>®</sup> DESCRIPTION

The OmegaFlex<sup>®</sup> MediTrac<sup>®</sup> flexible Corrugated Medical Tubing (CMT) system consists of a corrugated copper alloy tubing with axially swaged brass fittings equipped with a stainless steel anti-tamper sleeve and copper tube stub; providing easy attachment to traditional copper tube systems and direct connection to piping system components. The MediTrac<sup>®</sup> system has a minimum design safety factor of 3.5X maximum operating pressure (647.5 psig) per NFPA 99-2018 section 5.1.10.1.4 (2) and has been tested to withstand temperature exposure of 1000°F.

### MEDITRAC<sup>®</sup> CMT MATERIALS


<u>TUBING MATERIAL:</u>	Corrugated medical tubing material conforms to ASTM B103, copper alloy UNS No. C51000 complying with the requirements of NFPA 99-2018 5.1.10.4 (2) and meets CGA G4.1 cleanliness requirements.
<u>JACKET MATERIAL:</u>	Low Density FR Polyethylene, Plenum Rated, with a maximum Flame Spread Index of 25 and a Smoke Density Index of 50 when tested in accordance with ASTM E84 testing procedure. Complying with the requirements of NFPA 99-2018 5.1.10.1.5.
<u>FITTING MATERIAL:</u>	Fittings are metallic; Yellow Brass: Copper Alloy No. CA360 or equivalent, cleaned to CGA G4.1, and comply with NFPA 99-2018 5.1.10.7.1.

### MEDITRAC<sup>®</sup> SYSTEM OPERATIONAL RATINGS

<u>MAXIMUM CONTINUOUS USE OPERATING PRESSURE:</u>	½, ¾, and 1": 185 PSIG
<u>MAXIMUM CONTINUOUS USE OPERATING TEMPERATURE:</u>	250 °F


### MEDITRAC<sup>®</sup> SWAGED SEALED FITTING COMPONENTS

Item	Description	Material
1.	Adaptor	CA360 Brass
2.	Anti-Tamper Sleeve	300 Series Stainless Steel
3.	Non-Removable Threaded Axial Swaging Tool	CA360 Brass
4.	Split Ring	Brass/Stainless Steel
5.	Jacket Lock	CA360 Brass
6.	Rear Swage Sleeve	CA360 Brass
7.	Treaded Driver	300 Series Stainless Steel



**MEDITRAC® TUBING SPECIFICATIONS**

MediTrac Size	1/2"	3/4"	1"
Corrugated Tubing ID (nom)	0.597	0.820	1.060
Jacket OD (nom)	0.875	1.125	1.375
Bend Radius	6	8	10



**MEDITRAC® TUBING SUPPORT AND SPACING**

MediTrac Corrugated Medical Tubing shall be supported from the building structure. Hangers and supports shall comply with MSS SP-58, *Pipe Hangers and Supports – Materials, Design, Manufacture, Selection, Application, and Installation*. Supports for MediTrac corrugated medical tubing shall be sized for copper tubing, except one size larger should be selected to fit over MediTrac jacket. Maximum support spacing is defined in table below.

MediTrac Size	1/2"	3/4"	1"
Copper Tube Size for Hanger	3/4"	1"	1-1/4"
Maximum Spacing (ft)	6	7	8

**MEDITRAC LISTINGS**

MediTrac® Corrugated Medical Tubing has been tested and listed, per the requirements of NFPA 99-2018 section 5.1.10.1.4 (2), to UL 1365.